



M2 PLUS

DISTANCE METER

TECHNICAL FEATURES M2 PLUS

M2 PLUS 50		M2 PLUS 100	
Max Measuring Range	50 m / 230 ft	Max Measuring Range	100m / 328 ft
Measuring accuracy	±2mm Typical	Tilt angles measurement	NO
Measuring unit displayed	mm / in / ft	Measuring accuracy	±2mm
Continuous measurement	Available	Measuring unit displayed	mm / in / ft
Area Measurement	Available	Continuous measurement	Available
Volume Measurement	Available	Area Measurement	Available
Pythagoras Measurement	Full model	Volume Measurement	Available
Addition/Subtraction Measurement	Available	Pythagoras Measurement	Full model
Minimum/Maximum Measurement	Available	Addition/Subtraction Measurement	Available
Maximum Storage	20times	Minimum/Maximum Measurement	Available
Black lighting	Available	Maximum Storage	30times
Button sound tip	Available	Black lighting	Available
Laser Class	Class II	Button sound tip	Available
Laser Type	635nm,<1mW	Laser Class	Class II
Auto turn-off laser	20s	Laser Type	635nm,<1mW
Auto Power-off	150 s	Auto turn-off laser	20s
Storage Temperature range	-20°C -60°C (storage) 0°C to 40°C (operation)	Temperature range	-20°C -60°C (storage) 0°C to 40°C (operation)
Storage Humidity	RH85%	Auto Power-off	150s
Battery	1.5V 3*AAA	Storage Humidity	RH85%
		Battery	1.5V 3*AAA

Specifications subject to change without notice

STONEX AUTHORIZED DEALER

STONEX® EUROPE srl

Via Cimabue 39 - 20851 Lissone (MB) Italy
Phone +39 039 2783008 Fax +39 039 2789576
www.stonexpositioning.com
info@stonexpositioning.com